



Max Pressure	250 bar	Intervention Tolerance	± 3,5	Tightening Torque	25 Nm
Electrical Load Type	48V / 4A 24V / 6A	Thermal Hysteresis	< 14 °C	Housing Material	Brass Hex 24mm
Fluid Temperature	-40 ÷ +150 °C			Standard Protection Level	.F0 Faston Connection - IP00 * See the attachment caps and connectors

Select specifications for product coding

1.	Threads (X1)				09	12	25					
					1/2" BSPP L1 13,5 mm	3/8" BSPP L1 13,5 mm	M22x 1,5 L1 13,5 mm					
2.	Switching Temperature	030	040	050	060	070	080	090	100	110	120	
		30° C	40° C	50° C	60° C	70° C	80° C	90° C	100° C	110° C	120° C	
3.	Electrical Condition										A	C
											Normally Open	Normally Closed
4.	Switching										S	D
											Rising Setup	Falling Setup
5.	Customizations <small>* See the attachment caps and connectors</small>				.F0	.01	.97		.98	.99	.XX	
					Faston Connection IP00	Protection Cap KT011 - IP54	Cable L. 250mm Conn. AMP Superseal 1.5 2 vie -IP67		Cable L. 250 mm Conn. Deutsch DT04-2P - IP67	Cable L. 250 mm Conn. Metri-Pack (MP280) - IP67	Customized product	

TF2

1.	2.	3.	4.	5.	6.	7.
----	----	----	----	----	----	----