



Max Pressure	200 bar	Fluid Temperature	-20 ÷ +80 °C	Housing Material	Brass
Supply Voltage	12÷24 Vdc	Intervention Tolerance	± 3,5	Supply Cable	1,00 m
Max Load	20 A	Tightening Torque	25 Nm	Standard Protection Level	Cable L. 250 mm Metri-Pack Conn. (MP280) - IP67 * See the attachment caps and connectors

Select specifications for product coding

1.	Threads (X1)					09 1/2" BSPP L1 13,5 mm	12 3/8" BSPP L1 13,5 mm	25 M22x 1,5 L1 13,5 mm
2.	Switch-on Temperature (°C)	030 30° C	040 40° C	050 50° C	060 60° C	070 70° C	080 80° C	090 90° C
3.	Switch-off Temperature (°C)	030 30° C	040 40° C	050 50° C	060 60° C	070 70° C	080 80° C	090 90° C
4.	Transition Time (Seconds)					A 15	B 30	C 60
5.	Electrical Condition						A Normally Closed	C Normally Closed
6.	Customization * See the attachment caps and connectors			.97 Cable L. 250mm AMP Superseal Conn. 1.5 2 vie -IP67	.98 Cable L. 250 mm Deutsch Conn. DT04-2P - IP67	.99 Cable L. 250 mm Metri-Pack Conn. (MP280) - IP67		.XX Customized product

TS1

1.	2.	3.	4.	5.	6.
----	----	----	----	----	----