



Overpressure limit	Brass - Diaphragm 15 bar Steel - Diaphragm 15 bar	Operating temperature	* See the guide to selection of diaphragms / seals		Standard protection level	.F0 Faston Connection - IP00 * See the attachment caps and connectors	
Working pressure	Brass - Diaphragm 10 bar Steel - Diaphragm 10 bar	Max Hysteresis	Diaphragm conf.	10% of full scale value			

Select specifications for product coding

1.	Setting Range							01	02	
								Diaphragm -100 :-500	Diaphragm -500 :-900	
2.	Electrical Load							4	5	
								12V / 100mA Gold plated	250Vac / 5A 48Vdc / 4A	
3.	Electrical Condition						S	A	C	
							SPDT Contact	Normally Open	Normally Closed	
4.	Housing Material						B	Z	I	W
							Brass	Galvanized Steel	Stainless Steel 303	Stainless Steel 316
5.	Seals				H	E	S	V	I	
					HNBR	EPDM	MVQ (silicone)	FKM	Stainless Steel Diaphragm	
6.	Threads (X1)	00	01	10	11	20	21	23	40	41
		1/8"BSPT L1 10 mm	1/4"BSPT L1 12 mm	1/8"BSPP L1 10 mm	1/4"BSPP L1 12 mm	M10x1 L1 10 mm	M10x1K L1 10 mm	M12x1.5 L1 12 mm	1/8"- 27NPT L1 10 mm	1/4" - 18NPT L1 12 mm
7.	Customizations		.F0	.01	.02		.97	.99	.XX	
	* See the attachment caps and connectors		Faston Connection - IP00	ProtectionCap KT011 - IP54	Protection Cap KT012 - IP65		Conn. AMP Superseal 1.5 2 ways - IP67	Conn. Metri-Pack (MP280) - IP67	Costumized product	
8.	Adjustments (bar)							S	D	
								Rising Setup	Falling Setup	

VR8

1.	2.	3.	4.	5.	6.	7.	8.
----	----	----	----	----	----	----	----