



<b>Overpressure limit</b>	Brass - Diaphragm	300 bar	<b>Max Hysteresis</b>	Piston version	15% of full scale value	<b>L2 Dimension</b>	Piston version	55 mm
	Steel - Piston	600 bar		Diaphragm version	10% of full scale value		Diaphragm version	51 mm
<b>Working pressure</b>	Brass - Diaphragm	180 bar	<b>Standard protection level</b>	.E0 DIN Connector EN 175301-803-A (DIN43650/A) - IP65		<b>MAX L2 Dimension</b>	Piston version	69 mm
	Steel - Piston	450 bar		* See the attachment caps and connectors			Diaphragm version	65 mm
<b>Operating temperature</b>	* See the guide to selection of diaphragms / seals					<b>Dimension L3</b>	Piston version	70 mm
							Diaphragm version	66 mm

Select specifications for product coding

1.	<b>Setting Range</b>	01 Diaphragm 0.3-1 Bar	02 Diaphragm 0.5-2 Bar	03 Diaphragm 1.5-10 Bar	04 Diaphragm 9-20 Bar	05 Diaphragm 15-50 Bar	06 Diaphragm 40-80 Bar	07 Diaphragm 50-100 Bar	08 Piston 40-150 Bar	09 Piston 100-250 Bar	10 Piston 120-300 Bar	
2.	<b>Electrical Load</b>										4 12V / 100mA Gold plated	5 250 Vac / 5A 48 Vdc / 4A
3.	<b>Type of Regulation</b>											S SPDT Contact
4.	<b>Adjustment option</b>										V Screw	P Knob
5.	<b>Seals</b>							H HNBR	E EPDM	S MVQ (silicone)	V FKM	
6.	<b>Threads (X1)</b>							00 1/8"BSPT L1 10 mm	01 1/4"BSPT L1 12 mm	10 1/8"BSPP L1 10 mm	11 1/4"BSPP L1 12 mm	
7.	<b>Customizations</b> * See the attachment caps and connectors									.E0 DIN Connector EN 175301-803-A (DIN43650/A) - IP65	.XX Customized product	
8.	<b>Adjustments (bar)</b>										S Rising Setup	D Falling Setup

PC3

1.	2.	3.	4.	5.	6.	7.	8.
----	----	----	----	----	----	----	----