



<b>Overpressure limit</b>	Brass - Diaphragm Steel - Diaphragm Steel - Piston	80 bar 300 bar 600 bar	<b>Operating temperature</b>	* Vedere la guida alla selezione delle membrane / tenute	<b>Standard protection level</b>	IP 67 * See the attachment caps and connectors
<b>Pressione di lavoro</b>	Brass - Diaphragm Steel - Diaphragm Steel - Piston	40 bar 180 bar 450 bar	<b>Max Hysteresis</b>	Piston version: 15% of full scale value Diaphragm version: 10% of full scale value	<b>Dimensione L2</b>	Version / .S0: Piston version 64 mm Diaphragm version 61 mm Version / .D0: Piston version 67 mm Diaphragm version 64 mm

Select specifications for product coding

1.	<b>Setting Range</b>	01 Diaphragm 0.3-1 Bar	02 Diaphragm 0.5-2 Bar	03 Diaphragm 1.5-10 Bar	04 Diaphragm 9-20 Bar	05 Diaphragm 15-50 Bar	06 Diaphragm 40-80 Bar	07 Diaphragm 50-100 Bar	08 Piston 50-150 Bar	09 Piston 100-250 Bar	10 Piston 40-300 Bar
2.	<b>Electrical Load</b>									4 12V / 100mA Gold Plated	5 250Vac / 5A 48Vdc/4A
3.	<b>Electrical Condition</b>									A Normally Open	C Normally Closed
4.	<b>Housing Material</b>							B Brass	Z Galvanized Steel	I Stainless Steel 303	W Stainless Steel 316
5.	<b>Seals</b>						H HNBR	E EPDM	S MVQ (silicone)	V FKM	I Stainless Steel Diaphragm
6.	<b>Threads (X1)</b>	00 1/8"BSPT L1 10 mm	01 1/4"BSPT L1 12 mm	10 1/8"BSPP L1 10 mm	11 1/4"BSPP L1 12 mm	20 M10x1 L1 10 mm	21 M10x1K L1 10 mm	23 M12x1.5 L1 12 mm	40 1/8"- 27NPT L1 10 mm	41 1/4" - 18NPT L1 12 mm	
7.	<b>Customizations</b> * See the attachment caps and connectors							.S0 AMP Superseal Connector 1.5 2 ways -IP67	.D0 Deutsch Connector DT04-2P - IP67	.XX Customized product	
8.	<b>Adjustments (bar)</b>									S Rising Setup	D Falling Setup

PR9

1.	2.	3.	4.	5.	6.	7.	8.
----	----	----	----	----	----	----	----