



Overpressure limit	Brass - Diaphragm Steel - Diaphragm	20 bar 20 bar	Operating temperature	*See the guide to selection of diaphragms / seals		Standard protection level	.E0 DIN Connector EN 175301-803-A (DIN43650/A) - IP65 * See the attachment caps and connectors	
Working pressure	Brass - Diaphragm Steel - Diaphragm	15 bar 15 bar	Max Hysteresis	Diaphragm conf.	10% of full scale value			

Select specifications for product coding

1.	Setting Range			01	02					
				Diaphragm -200 : -500	Diaphragm -500 : -900					
2.	Electrical Load			4	5					
				12V / 100mA Gold plated	250Vac / 5A 48Vdc / 4A					
3.	Electrical Condition					S SPDT Contact				
4.	Housing Material			B	Z	I	W			
				Brass	Galvanized Steel	Stainless Steel 303	Stainless Steel 316			
5.	Seals			H	E	S	V	I		
				HNBR	EPDM	MVQ (silicone)	FKM	Stainless Steel Diaphragm		
6.	Threads (X1)	00	01	10	11	20	21	23	40	41
		1/8"BSPT L1 10 mm	1/4"BSPT L1 12 mm	1/8"BSPP L1 10 mm	1/4"BSPP L1 12 mm	M10x1 L1 10 mm	M10x1K L1 10 mm	M12x1.5 L1 12 mm	1/8"- 27NPT L1 10 mm	1/4" - 18NPT L1 12 mm
7.	Customizations							.E0	.XX	
	* See the attachment caps and connectors							DIN Connector EN 175301-803-A (DIN43650/A) - IP65	Customized product	
8.	Adjustments (bar)							S	D	
								Rising Setup	Falling Setup	

V27

1.	2.	3.	4.	5.	6.	7.	8.
----	----	----	----	----	----	----	----